

Safety factor 4:1
Sicherheitsfaktor 4:1
Factor de seguridad 4:1
Facteur de sécurité 4:1
Fattore di sicurezza 4:1




[EN] Double slings made of Grade 100 chain, complete with master link, chain length adjusting hook and lifting hook

[D] 2-Strang-Anschlagkette, Güteklasse Grad 100 mit eingeschweißtem Aufhängering und Verkürzerhaken, Lasthaken mit Sicherung

[E] Eslingas de cadena doble, cadena de Grado 100, completo con campanilla con gancho de ajuste de la cadena y gancho de elevación

[F] Élingue de chaîne double de degré 100, équipée d'une cloche avec crochet de réglage de la chaîne et crochet de levage

[I] Tirante doppio a catena di Grado 100, completo di campanella con gancio di regolazione catena e gancio di sollevamento

art.	ø mm	W.L.L. - Nutzlast - Carga útil - Charge utile - Portata [daN]			A x B x C			D x E	
					A mm	B mm	C mm	D mm	E mm
		60°	90°	120°					
XCN2G100825	8	4.200	3.500	2.500	135	75	18	95	34
XCN2G1001040	10	6.800	5.600	4.000	160	90	22	110	40
XCN2G1001365	13	11.000	9.500	6.500	180	100	26	136	51
XCN2G10016100	16	17.000	14.000	10.000	200	110	32	155	56
XCN2G10020160	20	27.200	22.040	16.000	300	160	40	185	60
XCN2G10022200	22	34.000	28.000	20.000	340	180	45	210	70