



[EN] Cable pulling grip with two eyes and thimble [D] Kabelziehstrumpf mit zwei Kauschen [E] Malla tiracables con doble lazo y dedales
[F] Chaussette tire-câbles à boucle double avec cosse coeur [I] Calza tiracavi con due asole con redancia

art.	ø mm	L mm	L ₁ mm				n.			kg
JST212/15	10-15	1450	1250	3.000 daN	5	1,50 mm		7	14 x 24	0,36
JST212/20	15-20	1450	1250	3.000 daN	5	1,50 mm		7	14 x 24	0,39
JST212/30	20-30	1450	1250	3.000 daN	5	1,50 mm		7	14 x 24	0,44
JST212/40	30-40	1450	1250	3.500 daN	6	1,50 mm		7	14 x 24	0,48
JST212/50	40-50	1450	1250	3.500 daN	6	1,50 mm		7	14 x 24	0,52
JST212/60	50-60	1450	1250	3.500 daN	6	1,50 mm		7	14 x 24	0,57
JST212/70	60-70	1500	1250	4.100 daN	7	1,50 mm		7	15 x 29	0,61
JST212/080	60-80	1500	1250	4.700 daN	8	1,50 mm		7	15 x 29	0,63
JST212/80	70-80	1500	1250	4.700 daN	8	1,50 mm		7	15 x 29	0,65
JST212/90	80-90	1500	1250	4.700 daN	8	1,50 mm		7	15 x 29	0,68
JST212/100	80-100	1550	1250	9.400 daN	8	2,00 mm		7	15 x 29	0,72
JT212/100	90-100	1550	1250	9.400 daN	8	2,00 mm		7	18 x 32	1,10
JST212/110	90-110	1550	1250	9.400 daN	8	2,00 mm		7	18 x 32	1,10
JT212/110	100-110	1550	1250	11.000 daN	10	2,00 mm		7	18 x 32	1,15
JST212/120	100-120	1550	1250	11.000 daN	10	2,00 mm		7	18 x 32	1,21
JT212/120	110-120	1550	1250	11.000 daN	10	2,00 mm		7	18 x 32	1,28
JST212/130	120-130	1550	1250	11.000 daN	10	2,00 mm		7	21 x 38	1,35
JST212/150	120-150	1550	1250	11.000 daN	10	2,00 mm		7	21 x 38	1,40
JST212/140	130-140	1550	1250	14.000 daN	12	2,00 mm		7	21 x 38	1,44
JT212/150	140-150	1550	1250	14.000 daN	12	2,00 mm		7	21 x 38	1,50

