



[EN] Cable pulling grip for underwater cables, with two eyes without thimble, laterally open, including two closing wires
 [D] Kabelziehstrumpf zum Verlegen von Seekabeln, mit zwei Schlaufen, seitlich offen mit zwei Bindelitzen
 [E] Malla tiracables para los cables submarinos, con doble lazo sin dedales, con un lado abierto y dos hilos de coser
 [F] Chaussette tire-câbles à lacet, avec boucle double, pour les câbles sous-marins, ouvert latéralement
 [I] Calza tiracavi per cavi sottomarini, con due asole senza redancia, lateralmente aperta con due fili di legatura

art.	ø mm	L mm	L ₁ mm				n.		[mm]	kg
XNCA065080	65-80	2700	2300	25.000 daN	6	3,2 mm		133	12 x 150	6,0
XNCA080100	80-100	3000	2500	33.000 daN	8	3,2 mm		133	14 x 200	9,0
XNCA100130	100-130	3200	2700	40.000 daN	10	3,2 mm		133	16 x 250	11,0
XNCA130150	130-150	4100	3500	65.000 daN	10	4,0 mm		133	20 x 330	22,0
XNCA150180	150-180	4800	4200	90.000 daN	10	4,8 mm		133	22 x 300	35,0
XNCA180220	180-220	5200	4500	110.000 daN	12	4,8 mm		133	24 x 350	42,0

