

NYLON, NON-CONDUCTIVE



[EN] Cable pulling grip for temporary junction, construction by non-conductive nylon wires [D] Kabelverbindungsstrumpf, gefertigt aus Nylon mit nicht leitender Eigenschaft [E] Malla tiracables para unión de alambre, construcción en hilos de nylon no conductor [F] Chaussette tire-câbles de liaison, construction en fils de nylon non-conducteur [I] Calza tiracavi di giunzione, costruzione in fili di nylon non conduttore

art.	ø mm	L mm	L ₁ mm				n.	kg
JM1520NNG	15-20	1400	700 + 700	1.200 daN	5	2,0 mm		0,33
JM2030NNG	20-30	1400	700 + 700	1.800 daN	5	2,0 mm		0,36
JM3040NNG	30-40	1600	800 + 800	2.200 daN	6	2,0 mm		0,40
JM4050NNG	40-50	1600	800 + 800	2.200 daN	6	2,0 mm		0,40
JM5060NNG	50-60	1600	800 + 800	2.200 daN	6	2,0 mm		0,40
JM6070NNG	60-70	1700	850 + 850	2.500 daN	7	2,0 mm		0,49
JM7080NNG	70-80	1700	850 + 850	3.000 daN	8	2,0 mm		0,52
JM80100NNG	80-100	1800	900 + 900	3.000 daN	8	2,0 mm		0,56

